

Other Specification for HDMI Output

UI Operation With USB Mouse

Image Capture 8M (3840*2160) JPEG Image in SD Card or USB Flash Disk

Video Record Video Format 8M(3840*2160) H264 Encoded MP4 Format

Video Recording Frame Rate 50~60 FPS(XCAM4K8MPA), 26~30 FPS(XCAM4K16MPA)(related with the SD card speed class and video resolution)

Camera Control Panel Including Exposure, Gain, White Balance, Color Adjustment, Sharpness and Denoising Control

Toolbar Including Zoom, Mirror, Comparison(Video~image, image~image, Freeze, Cross, Browser Function

Other Specification for GE Output

White Balance Auto/Manual/ROI White Balance

Colour Technique Ultra-Fine Color Engine (USB)

Capture/Control API Standard network API for Windows/Linux/Mac(USB)

Recording System Still Picture or Video

Software Environment (for USB2.0 Connection)

Operating System Support Windows 8/10 & 11 (32 & 64 bit), OSx (Mac OS X) & Linux

PC Requirements CPU: Equal to Intel Core2 2.8 GHz or Higher

Memory: 4 GB or More

Ethernet Port: RJ45 Ethernet Port

Display: 19" or Larger

CD-ROM

Operating Environment

Operating Temperature -10~ 50 °C

Storage Temperature -20~ 60 °C

Operating Humidity 30~80% RH

Storage Humidity 10~60% RH

Power Supply DC 12 V/2 A Adaptor

Overall Dimensions

Width x Depth x Height 98.3 mm (3.87") x 65 mm (2.56") x 78mm (3.07")

Shipping Weight 0.47 kg (1.0lbs)